



SI-10/12/15/18 Infrared Touchless Sensor











- Diameter of 19mm ,22 mm or 38mm to accommodate and mount in different panels.
- Specially designed to prevent any interference from other infra-red.
- Infrared proximity has a total lifespan of 100,000 hours.
- Standalone use. Optional panel available to select.
- Activate without pressing to prevent any disease contagion. It is suitable for access control system that widely used in public areas such as hospitals or restaurants. It is also can be used as auto-control detection.
- Built-in micro controller with power on self testing function. Adjustable proximity distance and door open delay time.

Specification


	SI-10	SI-12	SI-15	SI-18	
Dimensions	ø19mm	ø19mm	ø22 mm	ø38 mm	
Maximum current DC 24V	30mA	30mA	35mA	45mA	
Weight	10g	21g	24.5g	50g	
Case	Polycarbonate Polycarbonate fireproof + Stainless Steel				
Power input	DC 12~24V ±10%				
Contact load	0.5A@AC120V / 1A@DC24V				
Range	4~15 cm (±25%)				
Output state	Trigger state (0.5~20sec) or toggle mode output N.C. & N.O. Output				
Output delay time	0.5~20 Seconds, set 20 sec as toggle mode				
Water resistant IP	IP65				
Life time	Relay mechanical lifespan:1000,000				
Infrared sensor	100,000 hours				
State indicator	Red and Green Double-colored LED light				
Operation temperature	-10℃ ~ 70 ℃				

Series Model


• SI-10: Ø19mm Polycarbonate fireproof • SI-12: Ø19mm #304 Stainless Steel case • SI-15: Ø22mm #304 Stainless Steel case • SI-18: Ø38mm #304 Stainless Steel case

	Package				
Single switch			□ • • • • • • • • • • • • • • • • • • •		
	Dimensions: 115×39×4.5mm	Dimensions: 115×70×4.5mm	Dimensions: 86×86×4.5mm		
SI-10	SI-20	SI-60	SI-80		
SI-12	SI-22	SI-62	SI-82		
SI-15	SI-25	SI-65	SI-85		
SI-18		SI-68	SI-88		


Application



Dimensions



Instruction



Long